

Li<sup>TE</sup> Industrial Range

## Li<sup>TE</sup> Industrial 1000/800 HV+

Total Energy Capacity [kWh] <sup>1</sup>	1000
80% DoD Energy [kWh]	800
90% DoD Energy [kWh]	900
Current Capacity [Ah]	1600
Max. & Cont. Charge and Discharge Current [A]	1600
Max. & Cont. Charge and Discharge Power [kW]	1000
Nominal Voltage [V]	640
Max/Min Operating Voltage [V]	710/570
Max. Inverter Capacity [kVA]	1000
Total Weight [tonne]	9
Height (upright against wall) [mm]	1550
Depth (from wall)	908mm
Length (width along wall) [mm]	5200
DC Cables (no. per electrode) [mm <sup>2</sup> ] <sup>3</sup>	2x185
Round Trip Efficiency	97-97%
Enclosure Details	Heavy duty custom aluminium enclosure. Container options - 6m up to 2 x 1400/1120 mode, 12m up to 4 x 1400/1120 models (shipping weight restrictions might require partial site assembly of battery for weight above 22T).
External Interface	CAN Bus
On-board Management	Full battery management system and internal trip protection
Human Interfaces	State of Charge Display (0 to 100%), Error light, Error Reset Button, Plug for Programming and data access with PC, main breaker
Protection	Shunt Trip Circuit Breaker sized to suit max current, can be tripped by BMS if critical fault, manual reset. Protection for overcurrent, cell under and over voltage, temperature, weak cell detection and other critical events
Battery Chemistry	Lithium Iron Phosphate (LiFePO <sub>4</sub> )
Cell Form Factor	Large Format heavy duty prismatic cells of 200Ah each and 3,2V nominal voltage, fully sealed with bolt on electrode connections
Battery Cooling	Natural Convection (heat generation is negligible inside the battery)
Suitable Ambient Temp [°C]	0°C to +40°C
Extreme Operating Temp [°C] <sup>4</sup>	-20°C to +60°C
Remote Monitoring	Real time data logging and transmission via WiFi to online portal of key battery information (optional)
Warranty <sup>5</sup>	10 years or 4000 cycles for average 80% DoD, and max 90% DoD
Service Life - Cycles	>16 years (>5 500 cycles) expected life at 80% DoD per cycle, >20 years (7 500 cycles) at 50% DoD

### Notes to Specification Sheet

- For capacity larger than 2,5MWh these models must be configured with two or more in parallel on the same DC bus or with separate DC bus with inverters linked on the AC bus.
- Higher power output available on request.
- Fly Leads 6m long as standard, power cable Red = Positive, Black = Negative, conductors in table refer to one electrode i.e. per positive and negative connections. Up to 8m long available at extra cost (must be specified in order). Note that these fixed DC cables exit the battery enclosure on the right-hand end near the floor. This is to suit the bottom entry design of the floor standing ATESS inverters. A cable trench is recommended (where possible) for routing this cable along with all the other cables going to and from the inverter(s).
- Charging below 0°C not permitted. Extended time above 45°C not recommended for optimal battery life.
- See Freedom Won warranty document for further detail.

LITHIUM BATTERY SOLUTIONS SINCE 2010

FROM YOUR TRUSTED BATTERY PARTNER

[freedomwon.co.za](http://freedomwon.co.za) | +27 (0) 10 597 7794

Contact your nearest Accredited Freedom Won Distributor or Reseller Installers for further sales and technical support. Website links below.

[VIEW DISTRIBUTORS AND RESELLERS](#)