

LITE 2 COMMERCIAL HV RANGE

Range Overview Specification Sheet

	Commercial 100/80 HV	Commercial 200/160 HV	Commercial 300/240 HV	Commercial 400/320 HV	Commercial 500/400 HV	Commercial 600/480 HV	Commercial 700/560 HV
Total Energy Capacity [kWh]	100	200	300	400	500	600	700
Energy, 80% DoD [kWh]	80	160	240	320	400	480	560
Energy, 90% DoD [kWh]	90	180	270	360	450	540	630
Current Capacity [Ah]	200	400	600	800	1000	1200	1400
Max/Cont. Charge and Discharge Current [A] ¹	200/200	400/300	800/700	800/700	800/700	800/700	800/700
Max & Cont. Charge and Discharge Power [kW] ¹	112	200	300	400	400	400	400
Nominal Voltage [V]	512	512	512	512	512	512	448
Max/Min. Operating Voltage [V]	568/456	568/456	568/456	568/456	568/456	568/456	504/350
Max Recommended Inverter Total Rated Power (cont.) [kVA]	120	200	300	400	400	400	400
Short Circuit Current [kA]	5	10	15	19	24	28	36
Battery Dimensions - H x W x D [mm] ²	1405x1636x365	1403x1600x721	1460x2420x730	1460x2940x730	1450x3520x730	1400x4460x730	1455x5200x730
Crated Dimensions - H x W x D [mm]	1600x1790x575	1555x1780x815	1575x2570x815	1584x3285x848	1575x3990x835	On-Site Build	On-Site Build
Battery Weight [kg]	800	1542	2370	3076	4400	5290	6180
Crated Weight [kg]	914	1664	2564	3300	On-Site Build	On-Site Build	On-Site Build
DC Connection (no. per electrode) [mm ²] ³	1x95mm ² Permopower	1 x 120mm ² Permopower	1 x 185mm ² Permopower	1 x 185mm ² Polybraid	1 x 185mm ² Polybraid	1 x 185mm ² Polybraid	1 x 185mm ² Polybraid
Round Trip Efficiency [%]	96-97						
Enclosure	3mm thick Aluminium, powder coated, tamper proof, indoor use						
Protection	Shunt Trip Circuit Breaker sized to suit max current, can be tripped by BMS if critical fault, manual reset. Protection for overcurrent, cell under and over voltage, temperature, weak cell detection and other critical events						
Control Interface	CAN Bus for diagnostics & troubleshooting. RJ45 Strictly for BMS & inverter communication						
Human Interface	On and Off buttons, State of Charge display (0 to 100%), error light, error reset button, USB plug for programming and data access with PC, main breaker						
On-board Management	Full battery management system and internal trip protection						
Battery Chemistry	Lithium Iron Phosphate (LiFePO4)						
Cell Form Factor	Large Format heavy-duty prismatic cells of 200Ah each and 3.2V nominal voltage, fully sealed in aluminium casing with laser welded electrode connections						
Battery Cooling	Natural convection (heat generation is negligible inside the battery)			Fan and louver cooling solution			
Suitable Ambient Temp [°C] ⁴	0°C to +35°C						
Extreme Operating Temp [°C]	-20°C to +60°C						
Remote Monitoring	Real time data logging and remote monitoring over Ethernet. Internet connection required						
Warranty ⁵	Standard Warranty: 10 years (or 6000 cycles) 80% DoD, 0.5C Max Discharge, 0.25C Max Charge, Max 25°C						
Service Life ⁵	>16 years (>5500 cycles) expected life at 80% DoD per cycle, >20 years (>7500 cycles) at 50% DoD						

Notes to Specification Sheet

The LITE Commercial high voltage range is available in two variants, namely the HV and HV+. The HV models are suitable for the ATESS HPS range of hybrid battery inverters and the HV+ is suitable for the PCS range of battery inverters and associated PBD DC.

- The maximum values given apply to both charge and discharge. For systems requiring more power, two or more batteries must be installed in parallel. Max current duration 5min every 10min. 1.5 x Max overload can be handled for 5 seconds. Current limits rated for 10°C to 25°C battery temperature. De-rating will apply outside this temperature range.
- Excluding protrusions.
- Leads 4.0m long as standard, power cable Red = Positive, Black = Negative, conductors in table refer to one electrode i.e. per positive and negative connections. Up to 8m long available at extra cost (must be specified in order). Note that the leads exit the battery on the right-hand side near the floor on all the LITE Commercial HV and HV+ models. This is to suit the bottom entry of the floor standing ATESS inverters. A cable trench is recommended for routing this cable along with all the other cables going to and from the inverter (a cable tray is an alternative).
- Charging below 0°C not permitted. Extended time above 35°C not recommended for optimal battery life.
- See Freedom Won Warranty document for further detail.

DISTRIBUTORS AND RESELLERS

Contact your nearest Accredited Freedom Won Distributor or Reseller Installer for further sales and technical support.

Plug into The Current Future

www.freedomwon.co.za